
Granite Cobble Setts Footpath A110.07



DESIGN STATEMENT

Silver granite cobble setts can be used in designated shared zone areas to subtly alert users (feeling & colour contrast) to the potential vehicles passing by.

In the overall design, granite cobble sett should be combined with smooth surface areas to allow access for pram and wheel chair.

APPLICABLE LOCATION

The treatment should be used in Coburg Activity Centre in the specified Shared Space. The setts should be used in conjunction with 'bluestone - granite flagstone' pavement.

COUNCIL STANDARD DRAWING

N/A

CROSS REFERENCE DOCUMENT

- Coburg Streetscape Masterplan
- Brunswick Public Realm Design Manual
- AS 1428.1-1998 Supply of concrete

STANDARD SPECIFICATION

Dimension: Setts should be 100x100mm and should match silver highlight flagstones in the shared zone areas.

Grout: 10mm max. grouted joints colour to match setts. Grout finish level 5mm below face.

SUPPLIER

N/A

MAINTENANCE

Road Maintenance Unit: Replace Sections of footpaths when damaged.

Street Cleansing Unit: Cleaning will be undertaken as per current schedule.

GENERAL NOTES

1. **Mix:** Concrete for paver base shall be ready mix in accordance with relevant Australian Standard and shall have a 28 day compressive strength of 25Mpa minimum.
2. **Grade:** The cross fall of footpaths should not exceed 1 in 40.
3. **Joints:** expansion joints should be provided at max. 15 metres intervals.

July 2019



Moreland City Council

A110.07 Granite Cobble Set Footpath

