

Bluestone Pitcher Semi Mountable Kerb A130.04



DESIGN STATEMENT

The bluestone pitcher semi mountable kerb is a traditional bluestone pavement edging in inner urban areas of Moreland.

APPLICABLE LOCATION

The bluestone pitchers semi mountable kerb is to be used when bluestone is the predominant kerb material in the streetscape context. The use of this detail should be limited to reinstatement or reconstruction of existing kerbs or included in traffic carriageway treatments in heritage areas where traffic movements across the kerb line are allowed, e.g. splitter islands, centre islands, etc.

COUNCIL STANDARD DRAWING

SD 214 Bluestone pitcher semi-mountable kerb

CROSS REFERENCE DOCUMENT

- Moreland Standard Specification Section 63: Bluestone Pitcher kerbs & Channels & Bluestone paving. See also Section 61: Concrete kerbs, Channels Footpaths & Crossings. Asphalt pavement Surface Tech Note: 210.1, Moreland Standard Specifications for Asphalt: Section 407, 417, 161 and AS 2150, 2008.

STANDARD SPECIFICATION

Standard size of the bluestone pitcher 150x200x300mm. (Approx.) Joints between bluestone pitchers to kept to a minimum (20mm wide max) flush filled with mortar grout.

Mortar mix: 1 part cement, 3 part sand 1/8 part black iron oxide colouring.

SUPPLIER

N/A

MAINTENANCE

Street Cleansing Unit: Cleaning will be undertaken as per current schedule.

Open Space Maintenance Unit: To be weed sprayed as required as part of the maintenance routine.

GENERAL NOTES

1. Joints between bluestone pitchers to be 200mm wide nominal, flush filled with mortar grout.



A130.04 Bluestone Pitcher Semi Mountable Kerb

