

# Bluestone Fully Mountable Kerb A130.05



GENERAL

## DESIGN STATEMENT

The bluestone pitcher fully mountable kerb has similar functions to bluestone pitcher semi mountable kerb but allows vehicle movement across the kerb with minimal discomfort.

## APPLICABLE LOCATION

The bluestone pitcher fully mountable kerb is to be used when bluestone is the predominant material in the streetscape context.

The use of this detail should be limited to re-instatement or reconstruction of existing kerbs or included in traffic calming treatment in heritage areas where a mountable kerb is required, e.g. splitter islands, centre islands.

## COUNCIL STANDARD DRAWING

SD 215 Bluestone pitcher fully-mountable kerb

## CROSS REFERENCE DOCUMENT

- Moreland Standard Specification Section 63: Bluestone pitcher kerbs & channels & bluestone paving. See also Section 83.

## STANDARD SPECIFICATION

**Size:** Standard size of the bluestone pitcher approx 150x200x300mm. Where required source appropriately sized recycled bluestone pitchers to match existing.

**Mortar:** Joints between bluestone pitchers to be kept to a minimum (20mm wide max), flush filled with mortar grout. Mortar mix: 1 part cement, 3 part sand, 1/8 part black iron oxide colouring.

## SUPPLIER

N/A

## MAINTENANCE

**Street Cleansing Unit:** Cleaning will be undertaken as per current schedule.

**Open Space Maintenance Unit:** To be weed sprayed as required as part of the maintenance routine.

## GENERAL NOTES

1. Joints between bluestone pitchers to be 20mm nominal, flush filled with mortar grout.

# A130.05 Bluestone Fully Mountable Kerb

