

Vehicle Crossing in Concrete Type 3 A170.05



GENERAL

DESIGN STATEMENT

The concrete vehicle crossing is a smooth and continuous surface that is economical, durable and easy to maintain and enables vehicular access from the street to private property. The design of this type of vehicle crossing is based on the use of SM2M kerb and channel and allows the crossing to be built without removing the corresponding section of kerb and channel. It is particularly useful in new submissions where crossings will be built not very long after the completion of kerb and channel. Council specifies the shape and construction details to protect Council's assets; however, it is up to the applicant to engage a qualified person to ensure that the levels of the crossing will allow appropriate access without the vehicle scraping. If this also requires alteration of the levels of the abutting Council assets, permission for this must be obtained from the relevant Council officer.

APPLICABLE LOCATION

The Concrete Vehicle crossing should be used where there are concrete footpaths and also where the kerb and channel of type SM2M (semi mountable). The vehicular crossing should be graded flush with existing kerb and channel and footpaths to create a continuous smooth surface. A vehicle crossing permit must be obtained from Moreland City Council to construct/alter/remove a vehicle crossing. These permits are issued under the powers granted by Clause 12, Schedule 10 of the *Local Government Act 1989*.

COUNCIL STANDARD DRAWING

Type 3 Reinforced Concrete Vehicle Crossing, SD 267.

CROSS REFERENCE DOCUMENT

- AS 1428 (Australian Standard for Access and Mobility).
- AS2890.1-2004 (Australian Standard for Parking Facilities – Off Street Parking).
- Moreland City Council Specifications: Sections 61 & 80.

STANDARD SPECIFICATION

Refer to Notes 1-11 as detailed in general notes.

SUPPLIER

N/A

MAINTENANCE

Street Cleansing Unit: Channel of vehicular crossing to be cleaned as per current schedule.

Roads Unit: Channel to be maintained.

Property Owner: The maintenance of vehicle crossings is the responsibility of the property owners.

GENERAL NOTES



1. A vehicle crossing permit is required.
2. Splay S: *1.00m for residential. *2.00m for industrial.
Thickness T: *125mm for residential. *175mm for industrial.
3. Concrete strength: 25MPa.
4. Contraction joints shall be provided in both directions maximum spacing 1500.
5. For industrial properties, provide a second SL72 fabric at the bottom of the crossing, 30mm cover.
6. Where the new crossing is jointed to an existing crossing, provide 12mm dowels 300mm long (150mm each side of the joint) spacing 400mm.
7. Council's inspection officer to have discretion to vary standard, depending on existing street conditions, that is: crossing shape, charcoal colour and the treatment of the street channel.
8. Charcoal coloured concrete, where specified, shall be by adding 'Abilox' black colour powder or equivalent into the premix concrete. The rate of powder is 8.3% by weight of cementitious binder (approx. 25kg per cubic metre of concrete).
9. Refer to Australian Standards 2890.1 to ensure vehicles are not subject to scraping.
10. To be used on VicRoads Main Roads and Highways as per VicRoads Supplement to the Austroads Guide to Road Design –Part 4- Intersections & Crossings-General.
11. Refer to Road Pavement Reinstatement in Front of New Vehicle Crossing SD 265E.

July 2019



Moreland City Council

A170.05 Vehicle Crossing in Concrete Type 3



	Width W		Splay S	Thickness T	Reinforcement
	Min.	Max.			
Residential	3.0m	4.0m	1.0m	125mm	SL72 top
Industrial	3.0m	6.0m	2.0m	175mm	SL72 top & bottom